

Something new is taking shape

Welcome to our new, comprehensive spreading technology offer!

With immediate effect, Vogelsang and BeTEC have combined their strengths in the field of slurry application booms and, under the Vogelsang-BeTEC brand, have created a new, comprehensive range to suit every application, every user and every budget.

New portfolio structure

The new product range is clearly structured into the following product categories

- „SideClosing“ trailing shoe applicator
- „BackClosing“ trailing shoe applicator
- Dribble bar applicators

All BackClosing applicators are also available in a dribble bar version.

Slurry macerators

In addition to the tried-and-tested ExaCut eccentric technology in the ECL, ECM and ECQ variants, various application systems are fitted with the OptiCut distributor featuring a spring-preloaded cutting unit.

Trailing shoe systems - SideClosing



BlackBird® Single (SideClosing)

- Working widths from 7.5 – 12 m
- RedLine or GreenLine version
- 1 x ExaCut or OptiCut slurry macerator



BlackBird® Light (SideClosing)

- Working widths from 12 – 15 m
- RedLine and GreenLine version
- 2 x ExaCut or OptiCut slurry macerator



BlackBird® Pro (SideClosing)

- Working widths from 12 – 18 m
- RedLine and GreenLine version
- 2 x ExaCut or OptiCut slurry macerator



XTrail (SideClosing)

- Working widths from 21 – 24 m
- 2 x OptiCut slurry macerator



XTrail Plus (SideClosing)

- Working widths from 27 – 30 m
- 4 x OptiCut slurry macerator



BlackBird® Max (SideClosing)

- Working width 30 m
- Flexible use in 21 m, 24 m, 27 m or 30 m
- 4 x ExaCut ECM slurry macerator

Trailing shoe systems - BackClosing



Stylo (BackClosing)

- Working widths from 6 – 9 m
- 1 x OptiCut slurry macerator



Hilly (BackClosing)

- Working widths from 10.5 - 12 m
- For tankers or self propelled vehicles
- 1 x OptiCut slurry macerator



UniSpread (BackClosing)

- Working widths from 6 - 12 m
- 1 x ExaCut ECL slurry macerator



Cameleon Light

- Working widths from 12 – 18 m
- For tankers or self propelled vehicles
- 2 x OptiCut slurry macerator



Cameleon

- Working widths from 12 – 30 m
- For tankers or self propelled vehicles
- 12 - 21 m: 2 x OptiCut slurry macerator
- 24 - 30 m: 4 x OptiCut slurry macerator

Dribble bar systems - SideClosing or BackClosing



SwingUp (SideClosing)

- Working widths from 7.5 – 18 m
- 7.5 - 9 m: 1 x ExaCut ECL slurry macerator
- 12 - 18 m: 2 x ExaCut ECL slurry macerator



SwingMax (SideClosing)

- Working widths from 21-36 m
- 21 - 30 m also available with BaseRunner/Trailing shoe
- 2 x ExaCut ECL slurry macerator
- 36 m: 2 x ExaCut ECL slurry macerator



BackPac (BackClosing, Umbilical)

- Working widths from 21-32 m
- 21 - 30 m also available with BaseRunner/Trailing shoe
- 2 x ExaCut ECL slurry macerator