



# VacUnit DP

The Pumping Station for Vacuum  
Wastewater Systems

VX136-105Q / 7.5 kW

**VOGELSANG**



# VacUnit DP

## Double Pumping Station VX136-105Q / 7.5 kW

The Vogelsang VacUnit is a compact and reliable vacuum pumping station for grey and black water collection in vacuum sewerage systems.

Used as a centralized pumping station the VacUnit maintains the vacuum required for the effluent transport within vacuum waste water collection systems.

Reliable Vogelsang VX-Pumps enable direct inline discharge of the waste water & air phase into the downstream waste water system. The multi-phase pumping concept of the VacUnit eliminates the need for additional vacuum collection tanks with separate vacuum and sewage pumps.

VacUnit DP versions are designed as double pumping systems. A duty/standby pump arrangement ensures reliable operation when one unit is out of service while simultaneous operation of both pumps enables critical peak load situations to be overcome.

VacUnits are provided as pre-fabricated & factory-tested skid units incl. pipe work manifold with required valves, fittings and controls.

### Advantages

- Integrated control with system visualization and touchscreen HMI
- Proven Vogelsang VX-Pumps creating vacuum and direct inline transport of waste water in one single operation
- High system availability through duty/standby pumping arrangement
- No need for bulky vacuum collection tanks or extra pumping equipment
- Simple & easy maintenance and inspection due to quick-service design
- Compact design, low space requirement
- Low-noise & smooth system operation
- Closed & uncomplicated pump station design

### Options

- Weatherproof, soundproof cabinet enclosure or containerised plant room for outdoor installation
- Electronic soft starters for a smooth power grid/drive start process
- Customised solutions for process data acquisition and remote monitoring
- Extension modules for additional plant equipment
- Heating & ventilation options to cater for ambient conditions



Illustration showing special equipment (optional)

Standard specifications	
Pumping unit	VX136-105Q 7.5 kW
No. of pumping units	2
Capacity up to	2x 60 m <sup>3</sup> /h
Vacuum range	0 to -0.60 bar (normal operation)
Differential pressure max.	2.0 bar
Power consumption (Single pump operation at Δp= 0.6 bar)	4.2 kW
Control	Integrated PLC incl. control elements & indicators 7" touchscreen HMI-interface with system visualisation Multilingual plain text process data & fault notification Voltage: 3-400 V, 50 Hz Cable grommet: max. Ø25 mm <sup>2</sup>
Pipe system	DP-pump connectors incl. ball type back flow preventer and isolation valves
Connector inlet	DN100 - axial restraint pipe coupling
Connector outlet	DN100 - axial restraint pipe coupling
Common base plate	Heavy duty mild steel galv. construction with pockets for forklift handling
Main dimensions LxWxH approx.	3000 x 1100 x 2000 mm
Weight approx.	1650 kg
Ambient temperatures	+5 to +40 °C
Ambient conditions	Indoor, moderate