


Dimensions

series: IQ112 base, type inline




Attention
space required for
maintenance work
W=30 inches min.,
40 inches recommended







size	pump dimensions	standard flange		weight [lb]				part number connectors					
								90° QuickFlange Connector		45°QuickFlange Connector		QuickFlange adaptor set	
IQ112 -	L [in]	DN [in]	ASME [lb]	1)	2)	3)	4)	part number	weight [lb]	part number	weight [lb]	part number	weight [lb]
81	42.42	4	B16.5 150	355	432	423	364						
114	43.72			384	461	452	392	CON1455	17.9	CON1454	15.7	CON1460	2.0

1) pump without connectors
2) pump with 90° connectors
3) pump with 45° connectors
4) pump with adaptor set



allowable horizontal forces: 550 N
allowable vertical forces: 550 N
allowable moments: 150 Nm





changes of dimensions reserved
dimensions without indication of
tolerances acc. to DIN ISO 2768, rough

Vogelsang USA
7966 State Route 44
P. O. Box 751
Ravenna, OH 44266 USA

VOGELSANG

©Copyright www.vogelsangusa.com

dimensions shown in inches
fabrication tolerance is ± .12"

drawing no.: MAS0331		R: F
drawn by: Lucks	date: 27.06.2013	
checked by:	date:	