VX186-368QD

The VX Series is our advanced line of pumps. You'll find VX pumps in many applications in agriculture, industry and municipalities. To minimize wear and maximize performance these pumps feature design innovations that you can only get from Vogelsang such as HiFlo Lobes, Blockring Cartridge Seals and adjustable housing segments.



VOGELSANG

HIFLO POSITIVE DISPLACEMENT ROTARY LOBE PUMPS

Run Dry Without Damage: Vogelsang pumps are warranted against damage from run dry for a period up to 30 minutes.

Complete Wet-End Rebuilds Inline: Change rotors, mechanical seals, lip seals, wear plates, and adjust housing segments with ease.

100% Pulsation Free Operation: Vogelsang HiFlo Rotors provide pulsation free operation through the entire range of pumping.

Maximum Mechanical Seal Life: Vogelsang pumps use a pressurized oil canister to maintain pressure inside a buffer chamber between the wetend and gear box. This pressure reduces the wear on the mechanical seals and help keep your pump at optimum performance.

Self Priming to 25' (Wet): With suction lifts to 25', Vogelsang pumps excel at the toughest suction lift applications.

Compact Size Reduces Expense: Small footprints equate to reduced construction and fabrication expense.

Unlimited Drive Options: V-Belt drives, Geared Motors with reducers, Close coupled hydraulic motors, air or submersible, Power Take Off. Vogelsang pumps offer unlimited drive options.

Low Noise Operation: Just 78db at 3 feet.

Excellent for Shear Sensitive Material: Our gentle pumping action coupled with 100% pulsation free operation makes Vogelsang the pump of choice for all your shear sensitive material pumping needs

MECHANICAL SPECIFICATIONS: STANDARD & OPTIONAL

Materials:

Bearing Housing: Gray Cast Iron (230-260 Brinell)

Front Cover: Gray Cast Iron (230-260 Brinell)

Front & Rear Wear Plate Options: Hardox (700 Brinell), Optional: Tungsten Carbide, Stainless Steel.

Pump Shaft: Carbon Steel (ASTM A470)

Shaft Sleeve: Stellite Coated Stainless Steel.

Housing Segment Options: Gray Cast Iron (750 Brinell), Optional: Tungsten Carbide, Stainless Steel.

Mechanical Seal Options: Component Seal, Duronite or Silicon Carbide. Block Ring Cartridge Seal, Duronite (standard in new pumps) or Silicon Carbide.

Rotor Core: Gray Cast Iron

Rotor Coating Options: SBR, NBR (standard in new pumps), SewageLine©, Viton, Werobust©, Steel, Stainless Steel.

Mechanical Specifications:

Connections: Suction, 10" Discharge, 10"

Weight: 815lbs.

Rotor Options: HiFlo 4-wing Lobes

Mounting & Drive Options: Inline Gear Motor, Piggy-Back V-belt, Hydraulic, PTO.

Housing Segment Options: Standard or Dynamic

Warranty, Testing & Quality Assurance:

Warranty: Municipal, 2 years, 100% parts and labor, including wear. Industrial & Agricultural, 1 year, manufacturer's defects.

Testing: Each pump is factory tested at the customers specified duty point at a suitable range of flow and pressure conditions in accordance with Hydraulic Institute Standards.

ISO 9001:2000 Certification: Vogelsang is a fully certified for the manufacture and repair of industrial pumping equipment.

©Vogelsang USA, Inc. All Rights Reserved.


VX186-368QD


PERFORMANCE SPECIFICATIONS

Series & Model	Capacity gpm	Capacity m3/h	Displacement gal/100rev	Displacement l/100rev	Max Solids in	Max Solids mm	Flange Size in	Flange Size mm	Max Pressure Q: psi	Max Pressure bar	Max Pressure QD: psi	Max Pressure bar	Max. Speed rpm 1/min
VX186-368	360-1760	80-400	376	1424	2.5	61	10	250	29	2	116	8	600

PERFORMANCE CURVES

lobe coating: NBR-HiFlo
starting torque: 4493 in lb






Values based upon water 70°F
1) required driving power at the pump shaft

DIMENSIONAL DRAWING

All dimensions in inches
except shaft diameter



©Vogelsang USA, Inc. All Rights Reserved.